



CUSHMAN®



## HAULER® PRO-X

GET MORE MILEAGE OUT OF EVERY WORK DAY.

Stand back and let the new Hauler® PRO-X raise your expectations on what a 72-volt AC powertrain can do. With its 50-mile range, silent operation and lifted suspension, the Hauler PROX will help you and your team work seamlessly without disrupting play. Outstanding energy efficiency, low operational costs and a dash that can accommodate everything from an iPad to a radio, the Hauler PRO-X is equipped for action. So throw a spreader in the bed, load up the crew and let's work!

**LET'S WORK.®**

**72V**  
AC  
ELECTRIC

**1200LB**  
TOW  
CAPACITY

**12 CU FT**  
CARGO  
BED

**900LB**  
LOAD  
CAPACITY



## CUSHMAN® HAULER® PRO-X



LONG-HANDLED TOOL ATTACHMENT



STANDARD ON BOARD CHARGER



HIGHER GROUND CLEARANCE



OPTIONAL ALUMINUM BED/POWER DUMP

### BODY & CHASSIS

|                |   |
|----------------|---|
| FRAME          | Welded Steel with DuraShield™ Powder Coat |
| BODY & FINISH  | Injection Molded TPO, Painted             |
| STANDARD COLOR | Forest Green                              |

### DIMENSIONS

|                         |                     |
|-------------------------|---------------------|
| OVERALL LENGTH          | 119 in (302.26 cm)  |
| OVERALL WIDTH           | 50 in (125.48 cm)   |
| OVERALL HEIGHT W/CANOPY | 77 in (196 cm)      |
| WHEEL BASE              | 78 in (197 cm)      |
| FRONT WHEEL TRACK       | 38.0 in (96.56 cm)  |
| REAR WHEEL TRACK        | 38.0 in (96.56 cm)  |
| GROUND CLEARANCE        | 7.2 in (18.29 cm)   |
| CARGO BOX CAPACITY      | 12 cu ft (0.340 m³) |

### POWER

|                    |  |
|--------------------|--|
| POWER SOURCE       | 72-Volts                                   |
| MOTOR TYPE         | AC Induction                               |
| HORSEPOWER (KW)    | 22.4HP (16.7 kW) - Measured at Peak Torque |
| ELECTRICAL SYSTEM  | 72 Volt                                    |
| BATTERY (QTY/TYPE) | Nine 8-Volt Deep Cycle                     |
| BATTERY CHARGER    | 900 Watt 72V DC                            |
| KEY OR PEDAL START | Pedal                                      |
| DRIVE TRAIN        | Motor Shaft Direct Drive                   |
| TRANSAXLE          | Differential with Helical Gears            |
| SPEED CONTROLLER   | 350 Amp AC                                 |
| GEAR SELECTION     | Forward-Neutral-Reverse                    |
| REAR AXLE RATIO    | 17:1                                       |

### PERFORMANCE

|                          |   |
|--------------------------|---|
| SEATING CAPACITY         | 2 Person                                    |
| CURB WEIGHT              | 1513 lb (686 kg)                            |
| BED LOAD CAPACITY        | 500 lb (227 kg)                             |
| VEHICLE LOAD CAPACITY    | 900 lb (408 kg)                             |
| SPEED                    | 16.5 mph +/- 0.5 mph (26.6 kph +/- 0.8 kph) |
| TOWING CAPACITY          | 1200 lb (544 kg) max                        |
| OUTSIDE CLEARANCE CIRCLE | 24.0 ft (7.3 m)                             |

### STEERING & SUSPENSION

|                       |  |
|-----------------------|--|
| STEERING              | Self-Compensating Rack and Pinion          |
| FRONT/REAR SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers  |
| SERVICE BRAKE         | Rear Wheel Mechanical Self-adjusting Drum  |
| PARKING BRAKE         | Self-compensating, Single Point Engagement |
| FRONT/REAR TIRES      | 20 x 8.10 (6 Ply Rated)                    |

### OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Flexible Tool Clamps
- L-Track Aluminum Bed System
- Tie Down D-Loops
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brushguard
- ROPS-Certified Ball Cage
- Weather Enclosure
- Rearview Mirror
- Color Options
- ROPS-Certified Cab