



EPT12-EZ



Electric Pallet Truck 1.2t

- Slightly difference on cost, completely different experience, from hand pallet truck to EZ truck!
- Standard Lithium Ion battery, life time maintenance free.
- CAN-BUS system simplify operation/maintenance level.

CE

EP
Let's grow together

EMOVEIT

BATTERY ELECTRIC TUGS, PUSHERS, PULLERS AND LIFTERS

www.emoveit.com.au

1300 213 010

FEATURE

- **Light service weight, decent capacity, suitable for anywhere a hand pallet truck could be used:**

120kg Ultra-light service weight, 1200kg high rated capacity, come and go freely in small working space with 1390mm turning radius.

- **CAN-BUS system:**

CAN-BUS system simplifies operation/maintenance level, improves system reliability.

- **Patented integrated design:**

Innovative designed sealed hydraulic unit, low noise, easy maintenance.

- **Patented non-contact limit switch design:**

New patented non-contact limit switch design, improves the reliability.

- **Safety:**

Convenient emergency stop switch, strong driving wheel cover, solid battery clip, ensure safety and reliability.

- **Battery:**

3.7kg battery replacement, optional standby battery extend run time.

- **Patented handle design:**

New design of integral handle head, easy to access all control buttons.

- **Patented frame design:**

New frame design, light service weight, high strength.


- **Patented key switch design:**

New patented key switch design, integrated with u-disk function.

- **Easy maintenance:**

Maintenance free truck design for end users to trouble shooting and replace failure part by simple instruction, free labor cost.

SMART panel reflect operation and trouble shooting status.



Electric Pallet Truck 1.2t

EPT12-EZ

Characteristics					
1.1	Manufacturer			EP	
1.2	Model designation		EPT12-EZ BASIC	EPT12-EZ PRO	
1.3	Power unit		Battery		
1.4	Operator type		Pedestrian	Pedestrian	
1.5	Load capacity	Q	kg	1200	1200
1.6	Load centre	c	mm	600	600
1.7	Axle centre to fork face	x	mm	950(880)	950(880)
1.8	Wheelbase	y	mm	1190(1120)	1190(1120)
Weights					
2.1	Service weight (include battery)		kg	116	130
2.2	Axle loading with load, driving side/loading side		kg	406/910	420/910
2.3	Axle loading without load, driving side/loading side		kg	96/20	110/20
wheels/tyres					
3.1	Tyre type driving w heels/loading w heels			PU/PU	PU/PU
3.2	Tyre size, driving w heels (diameter×width)		mm	Φ130x55	Φ210x70
3.3	Tyre size, loading w heels (diameter×width)		mm	Φ80x60(Φ74x88)	Φ80x60(Φ74x88)
3.4	Wheels, number driving/loading (x=drive w heels)		mm	1x/4(1x/2)	1x/4(1x/2)
Dimensions					
4.1	Lift height	h ₃	mm	115	115
4.2	Height of tiller arm in driving position, min./max.	h ₁₄	mm	750/1190	750/1190
4.3	fork height, low/ered	h ₁₃	mm	80	80
4.4	Overall length	l ₁	mm	1540	1540
4.5	Length to fork face	l ₂	mm	390	390
4.6	Overall width	b ₁	mm	560(685)	560(685)
4.7	Fork dimensions	sxexl	mm	53x150x1150	53x150x1150
4.8	Distance between fork-arms	b ₅	mm	560(685)	560(685)
4.9	Ground clearance, center of wheelbase	m ₂	mm	27	27
4.10	Aisle width for pallets 1000 × 1200 crossways	Ast	mm	1640	1640
4.11	Aisle width for pallets 800 × 1200 lengthways	Ast	mm	1840	1840
4.12	Turning radius	Wa	mm	1390	1390
Performance					
5.1	Travel speed, with/ without load		km/h	3.8/4	4/4.5
5.2	Lifting speed, with/ without load		m/ s	0.02/0.025	0.02/0.025
5.3	Lowering speed, with/ without load		m/ s	0.06/0.03	0.06/0.03
5.4	Max. gradeability, with/ without load		%	2/8	4/10
5.5	service brake			electric	electric
Drive					
6.1	Drive motor rating 60 min		kW	0.45	0.65
6.2	Lift motor rating at 15%		kW	0.5	0.5
6.6	power consumption according to VDI cycle		KWh/h	0.16	0.25
others					
7.1	Type of drive control			DC	DC
7.2	Noise at the driver's ear			<74	<74
7.3	Application			INDOOR	GENERAL

- The parameters in the table are of the standard model. For more information, please contact us.
- The parameters are subject to change without notice.

	EPT-12EZ
Standard configuration	24V 20Ah
Battery pack capacity	24V 20Ah/26Ah
Chemical Material	NMC
Pack weight(Kg)	3.7/5
Charging	24V10A
Pack dimension (including BMS)mm	200*90*260/200*90*295

Lithium battery with external charger will equipped with battery connector.

Electric Pallet Truck 1.2t

